



Berth and draft restrictions for Port of Gävle

Chart datum: mean sea level +/- 0,0 m RH2000.

ViVa Bönan, the wind- and sea level station showing current sea level for Port of Gävle.

Fairway/Berth	Water depth (m)	Max. draft (m)	Max. breadth (m)	Max. LOA (m)	Misc.	Ref.
Holmuddsrännan (channel)	13,4	12,2	42			1
Fredriksskans 1	9,1	8,6	28	190		
Fredriksskans 2-3	6,2	6,0			Tug quay	
Fredriksskans 4	7,0	6,5				
Fredriksskans 5-6	7,6	7,1				
Fredriksskans 7	8,7	8,2				2
Fredriksskans 8	8,0	7,5				
Fredriksskans 9-12	9,2	8,7	28	190	Length of berth 318 m	
Fredriksskans 12-14	8,6	8,1	28	190	At green quay mark	
Fredriksskans 16	8,8	8,3				
Fredriksskans 17-19	10,5	10,0	28	190		3
Fredriksskans 23-25	13,4	12,2				
Fredriksskans 27	13,4	12,9				4
Granudden 301-303	10,7	10,2			Length of berth 325 m	
Fairway to Karskär					UKC 0,7 m	5

1. If vessel breadth ≥ 30 m 2 pilots are required.
2. 100 meters from the west corner of berth.
3. Maximum combined length of two vessels alongside is 308 m.
4. On arrival and departure, the maximum draft is 12,2 meters.
5. Please contact the owner of the port for current berth draft.
6. Generally, the minimum UKC in fairways in port of Gävle is 0,7 m + dynamic UKC in the form of squat, swell (pitch) and heel.

[Port rules and regulations etcetera](#)

Date: 230425

Switchboard +46 26 17 88 43
E-mail info@gavlehamn.se

Depåvägen 20
SE-806 47 Gävle, Sweden
www.gavlehamn.se