



## Berth and draft restrictions for Port of Gävle

Chart datum: mean sea level +/- 0,0 m RH2000.

ViVa Bönan, the wind- and sea level station showing current sea level for Port of Gävle.

Fairway/Berth	Water depth (m)	Max. draft (m)	Max. breadth (m)	Max. LOA (m)	Misc.	Ref.
Holmuddsrännan (channel)	13,4	12,2	42			1,7
Fredriksskans 1	9,5	9,0	28	160	Temporary limitation on vessel LOA	8
Fredriksskans 2-3	6,2	6,0			Tug quay	
Fredriksskans 4	7,0	6,5				
Fredriksskans 5-6	7,6	7,1				
Fredriksskans 7	8,7	8,2				2
Fredriksskans 8	8,0	7,5				
Fredriksskans 9-12	9,2	8,7	28	190	Length of berth 318 m	
Fredriksskans 12-14	8,6	8,1	28	190	At green quay mark	
Fredriksskans 16	8,8	8,3				
Fredriksskans 17-19	10,5	10,0	28	190		3
Fredriksskans 24-25	13,4	12,2				
Fredriksskans 27	13,4	12,9				4,5
Granudden 301-303	10,7	10,2			Length of berth 325 m	
Fairway to Karskär					UKC 0,7 m	6

1. If vessel breadth  $\geq 33$  or LOA  $\geq 210$  meter 2 pilots are required.
2. 100 meters from the west corner of berth.
3. Maximum combined length of two vessels alongside is 308 m.
4. On arrival and departure, the maximum draft is 12,2 meters.
5. LOA restrictions according to Operating instructions, energy port
6. Please contact the owner of the port for current berth draft.
7. Generally, the minimum UKC in fairways in port of Gävle is 0,7 m + dynamic UKC in the form of squat, swell (pitch) and heel.
8. Temporary vessel length restriction of a maximum of 160 meters LOA, See port notice quay 1

<https://gavlehamn.se/EN/Port-rules-and-regulations>

Date: 241127

